

Glidevale Protect

2 Brooklands Road, Sale,
Cheshire, M33 3SS

T +44 (0)161 905 5700

F +44 (0)161 905 2085

E info@glidevaleprotect.com

W glidevaleprotect.com

PMP31 Issue 2 December 2022

Roofing Accessories

Underlay Protectors

Protect OFV Eaves Skirt

The Protect OFV Eaves Skirt replaces both the underlay into the gutter and the traditional tilting fillet and will not rot in the gutter unlike bitumen derivatives. Used to avoid sagging and ponding of the underlay behind the fascia and ensure correct water discharge into the gutter.

Eaves skirt to be manufactured from robust UV stabilised PVC-U construction and designed to resist impact and UV degradation over time. Eaves skirt to be designed to be suitable for new build and refurbishment applications with the ability to be used in conjunction with fascia vents or fixed directly onto the fascia board. Product to provide a flexible design to allow access to the fascia board for fitting gutter brackets.

Eaves Skirt to be compliant with Building Regulations Approved Document C and BS 5534.

Product to be installed as per manufacturer's fixing instructions

Manufacturer: Glidevale Protect, a division of Building Product Design, 2 Brooklands Road, Sale, Cheshire, M33 3SS, United Kingdom. Tel: +44 (0)161 905 5700, Fax: +44 (0)161 905 2085. E-mail: info@glidevaleprotect.com Website: glidevaleprotect.com/eavesskirt

STA Assured Gold accredited company and associate members of the Structural Timber Association (STA) The Modular and Portable Build Association (MPBA), The Irish Timber Frame Manufacturers' Association (ITFMA) and the Offsite Alliance (OA).

Product Reference: Protect OFV Eaves Skirt

Underlays

Protect VP200:

Protect VP200 is a highly vapour permeable roof underlay, produced in the UK. A 'Type LR' underlay, it offers low vapour resistance to exceed BS 5250:2021 requirements whilst remaining completely airtight. Protect VP200 is CE & UKCA marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: Zones 1-2 in accordance with BS 5534:2018.

Glidevale Protect

2 Brooklands Road, Sale,
Cheshire, M33 3SS

T +44 (0)161 905 5700

F +44 (0)161 905 2085

E info@glidevaleprotect.com

W glidevaleprotect.com

Protect VP300:

Protect VP300 is a highly vapour permeable roof underlay, produced in the UK. A 'Type LR' underlay, it offers low vapour resistance to exceed BS 5250:2021 requirements whilst remaining completely airtight. Protect VP300 is CE & UKCA marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: Zones 1-3 in accordance with BS 5534:2018.

Protect Zytec:

Protect Zytec is a highly vapour permeable roof underlay, produced in the UK. A 'Type LR' underlay, it offers low vapour resistance to exceed BS 5250:2021 requirements whilst remaining completely airtight. Protect Zytec is CE & UKCA marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: Zones 1-4 in accordance with BS 5534:2018.

Protect VP400:

Protect VP400 Plus LR is a highly vapour permeable roof underlay, produced in the UK. A 'Type LR' underlay, it offers low vapour resistance to exceed BS 5250:2021 requirements whilst remaining completely airtight. Protect VP400 PLUS LR is CE & UKCA marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: unrestricted use across the UK and Ireland (Zones 1-5) in accordance with BS 5534:2018.

Protect A1 T3:

Protect A1 T3 is an impermeable roof underlay, produced in the UK. A 'Type HR' underlay, it offers high vapour resistance and complete airtightness and developed to overcome the disadvantages of Type 1F and 5U felts and second generation plastic sheet materials. Protect A1 T3 is CE & UKCA marked and is suitable for use in all pitched roofs. Resistance to wind uplift: unrestricted use across UK and Ireland (Zones 1-5) in accordance with BS 5534:2018.

Protect A1:

Protect A1 is a third generation impermeable roof underlay, produced in the UK. A 'Type HR' underlay, it offers high vapour resistance and complete airtightness and developed to overcome the disadvantages of Type 1F and 5U felts and second generation plastic sheet materials. Protect A1 is CE & UKCA marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: unrestricted use across UK and Ireland (Zones 1-5) in accordance with BS 5534:2018.

Protect Wunderlay:

Protect Wunderlay is an impermeable roof underlay, produced in the UK. A 'Type HR' underlay, it offers high vapour resistance and complete airtightness and developed to overcome the disadvantages of Type 1F and 5U felts and second generation plastic sheet materials. Protect Wunderlay is CE marked and independently approved by BM TRADA, with a Q Mark certification and is suitable for use in all pitched roofs. Resistance to wind uplift: Zones 1-4 in accordance with BS 5534:2018.